


PRODUCT CODE: RTBP522P2-M40WCO-WH
2X2 LED BACK LIT PANEL/MULTI-WATTAGE/3CCT


PRODUCT DESCRIPTION

The new Etlin-Daniels generation of RTBP522P2-M40WCO-WH 2 x 2 LED Back Lit Flat Panel offers excellent, flicker-free lighting, increased energy savings and greatly reduced maintenance over traditional fluorescent troffers. The PMMA lens provides for even and glare-free illumination over the fixture's life.

This new P2 generation is available in 120-347V and also features multi-wattage and 3CCT switching for the utmost in convenience, reducing inventory stress while also eliminating contractor installation issues with either wrong color or wattage. And this new P2 generation is 125lm/w efficacy - DLC5.1 Premium for best available utility rebate status.

There are 4 mounting options available - recessed in t-bar, recessed drywall, surface mount or suspended. For further energy savings, take advantage of the available 0-10V Continuous Dimming.

The new Etlin-Daniels RTBP5P2-M Series is the perfect compliment for any office, educational, healthcare, commercial or industrial applications, whether they are employed to retrofit or upgrade an existing site, or installed in a new build.

FEATURES

- Indoor LED Light Source
- Light weight, durable aluminum and polycarbonate housing.
- PMMA surface illumination for glare free uniformity.
- Flicker free performance.
- 4 mounting options - recessed t-bar, recessed drywall, surface & suspended
- 120-347V / 125lm/w
- Multi-wattage - 25W / 30W / 40W
- 3CCT - 3500K / 4000K / 5000K
- Damp Location rated
- Earthquake clips for secure recessed applications
- 0-10V Continuous Dimming
- 5 year warranty
- L70 - 50,000 hours.
- DLC5.1 Premium


SOLD IN PACKAGES OF 2 UNITS

PRODUCT SPECIFICATIONS (OPTICAL DATA)

PRODUCT SPECIFICATIONS (ELECTRICAL DATA)

LED TYPE	LED QTY	WATTAGE	COLOR TEMPERATURE	LUMENS	SYSTEM EFFICACY	CRI	BEAM ANGLE	POWER EFFICIENCY	POWER FACTOR	HARMONIC DISTORTION
RUNLITE 2835	96 CHIPS	25W - 3500K - 3278 LM / 4000K - 3204 LM / 5000K - 3310 LM 30W - 3500K - 3751 LM / 4000K - 3866 LM / 5000K - 3769 LM 40W - 3500K - 5003 LM / 4000K - 5092 LM / 5000K - 5012 LM			125 - 132 LM/W	>80 CRI	110°	>88%	>0.90	<15%

PRODUCT SPECIFICATIONS

VOLTAGES	POWER FREQ.	FIXTURE MATERIAL	LIFE SPAN	STORAGE TEMP	OPERATING TEMP	PRODUCT DIMENSIONS	CARTON SIZE	
120-347V	50-60HZ	ALUMINUM	>50,000 HOURS	-25°C~40°C -13°F~104°F	-25°C~40°C -13°F~104°F	23.7 X 23.7 X 1.2 INCHES (602 X 602 X 30 MM)	25 X 3.34 X 25 INCHES (635 X 85 X 635 MM)	

ADDITIONAL INFORMATION

INSTALLATION METHOD

RECESSED/SURFACE/SUSPENDED

FIXTURE COLOR

WHITE ALUMINUM FRAME

CONTROL TYPE

0-10V CONTINUOUS DIMMING

PRODUCT CODE: RTBP522P2-M40WC0-WH
2X2 LED BACK LIT PANEL/MULTI-WATTAGE/3CCT


DLC LISTING

ED Model Number	Technical Requirements Version	Product ID	Listed Model Number	Category	Primary Use Designation
RTBP522P2-M40WC0-WH	DLC 5.1 Premium	S-V7H0NG	RTBP522P2-M40WC0-WH	Indoor Luminaires	1x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
RTBP522P2-M40WC0-WH	DLC 5.1 Premium	S-SG8W5F	RTBP522P2-M40WC0-WH	Indoor Luminaires	Low-Bay Luminaires for Commercial and Industrial Buildings

CERTIFICATIONS



CAN ICES-005 (B) / NMB-005 (B)

DRIVER/LED CHIP



MOUNTING OPTIONS



CABLE SUSPENSION KIT FOR FLAT PANEL -
SUSPENSION CABLES 1 METER IN LENGTH.
PART#: RTBP5SPK-M



DRYWALL KIT
FOR RTBP522-M / RTBP522P-M
PART#:RTBP5DWK-22M



SURFACE MOUNT KIT
FOR RTBP522-M / RTBP522P-M
PART#:RTBP5SMK-22M

WARNING - BACK LIT FLAT PANELS REQUIRE BACK LIT SURFACE MOUNT KITS.

ORDERING INFORMATION - RTBP5 SERIES

SERIES	SIZE	PREMIUM	WATTS	VOLTAGE	COLOR TEMPERATURE	DIMMABLE	FINISH
E.G. RTBP5	22	P2	M40	W	C	0	WH
RTBP5 - BACKLIT PANEL	22 - 2X2	P2 - PREMIUM	M40 - MULTI-WATTAGE	W - 120-347V	C - CHANGEABLE COLOR	0 - 0-10V	WH - WHITE
5 SERIES			25W / 30W / 40W		3500K / 4000K / 5000K	CONTINUOUS DIMMING	

Head Office - 1850 Wilson Ave. · Toronto, ON · M9M 1A1 · **Tel:** 416.741.7336 · **Fax:** 416.741.9104

Toll Free: in Canada. 1.800.661.9610 · in USA. 1.888.762.5384 (SOCKETS4U)

www.etlin-daniels.com · For sales/service questions - sales@etlin.com