

LEDBAR-CCT

LED Fluorobar, 290-1850 Lumens, 5-22W, Colour Selectable

Cove, Under Cabinet & Millwork

	Job Information	
Project Name		Туре
Location		
Quantity		Date
Contact/Phone		
Notes		

Features

Housing

Durable extruded aluminum frame with frosted smooth lens. Suitable for dry location applications only. On-body ON/OFF switch and a 5-position 2700-5000K CCT select switch are provided for individual control.

LED Driver

Fixture is provided with built-in silent non-flicker electronic LED driver, 120V, 50 / 60Hz.

Light Output

Providing up to 1850 lumens, and up to 96lm/W, this undercabinet fixture also features a 5-position 2700-5000K CCT select switch.

Dimming

Fixture is 100~0% dimmable with industry standard TRIAC and ELV dimmers.

LED Characteristics

Powered by LED integrated strip that maintains uniform intensity with 70%

lumens at 60,000 hours with a rated life of 36,000 hours average life; at 90 CRI.

Beam Spread

The fixture lens provides for 125° beam spread.

Linkind

Complete with a joiner, these no shadow linking fixtures can be linked up to 2500 mA / 300 W.

Mounting Kit

Hardware provided for mounting fixture to standard horizontal surfaces or vertical wall surface.

Operating Temperature

-18°C~40°C (0°F~104°F).

Rating


Suitable for use in closets. Compliant with NFPA 70, NEC section 410.16 (A)(1). Maintain a minimum of 6" clearance to combustible materials at all times.

SPECIFICATION					
Approved Location	Dry				
Beam Angle	125°				
	2700 K / 3000 K /				
CCT	3500 K / 4000 K /				
	5000 K				
Certification	cULus				
Connection Type	3-Wire				
CRI	90+				
Dimming	Yes				
Dimming Technology	TRIAC / ELV				
Lumens	Up to 1850				
Lumens per watt	Up to 96				
Min. Start Temp.	-18°C				
Lumen Maintenance	70% @ 60,000 hrs				
Power Factor	>0.95				
Rated Life	36,000 hrs				
THD	<15				
Voltage	120V				
Warranty	3 Years				
Wattage	Up to 22				



Description

This LED Fluorobar light is a linear light with an integrated LED strip. Available with various lengths featuring ON/OFF and CCT Select switch to meet any installation application.



		LEDBAR14-CCT	LEDBAR23-CCT	LEDBAR34-CCT	LEDBAR46-CCT	LEDBAR58-CCT
Length (L)		131/2"	225/8"	347/16"	463/16"	58"
		343mm	574mm	874mm	1174mm	1474mm
Wattage (W)		5	9	14	18	22
Lumens	2700 K	250	550	850	1000	1200
	3000 K	400	775	1175	1500	1800
	3500 K	350	705	1120	1400	1600
	4000 K	400	775	1175	1500	1800
	5000 K	400	775	1175	1500	1800










Ordering Guide

LEDBAR



58:58", 22W

Notes

Accessories are sold separately. For additional options consult your Liteline representative.

Due to our continued efforts to improve our products, product specifications are subject to change without notice.

Liteline Corporation Copyright © 2025 All rights reserved. Telephone 416.996.1856 1.866.730.7704 Fax 905.709.5255 1.888.738.9736



Power Cord



ALFT6000-WH-3

6' Flexible 3-wire power cord for FluoroBar series.



ALFT6000S-WH-3

6' Flexible 3-wire power cord with on/off switch, for FluoroBar series.



ALFT6016-WH-3

16" Flexible 3-wire power cord for FluoroBar series.

Power Cord with 90° Connector



ALFT60901-WH-3

ALFT60904-WH-3

6' Flexible 3-wire power cord with 90° connector (top connection).

6' Flexible 3-wire power cord with 90° connector (right connection).



ALFT60902-WH-3

6' Flexible 3-wire power cord with 90° connector (left connection).



ALFT60903-WH-3

6' Flexible 3-wire power cord with 90° connector (bottom connection).

Hardwire Box



ALFT6300-WH

Hardwire box for FluoroBar series, with on/off switch.



ALFT6300-OS-WH

LEDBAR hardwire with motion sensor.



ALFT6300-PIR-WH

LEDBAR hardwire with PIR motion sensor.

Flexible Cord with 90° Connectors



ALFT90-WH-3

ALFT903-WH-3 6" Flexible 3-wire cord with 90° connectors (right connection).

6" Flexible 3-wire cord with 90° connectors (top connection).



ALFT901-WH-3

6" Flexible 3-wire cord with 90° connectors (left connection).



ALFT902-WH-3

6" Flexible 3-wire cord with 90° connectors (bottom connection).

Flexible Connectors



FBT6106-WH-3

FBT6136-WH-3

6" Flexible 3-wire connector.



FBT6100-WH-3

12" Flexible 3-wire connector.



FBT6124-WH-3

24" Flexible 3-wire connector

36" Flexible 3-wire connector

Clips



LEDBAR-MAGCLIP-3

Magnetic mounting clips for LEDBAR, 3-pack.



LEDBAR-CLIPS-90

90° mounting clips for LEDBAR, 2-pack.