



Project / Job Name:

Location:

Fixture Type:

Notes:

**62-700** - 14 Watt 18 Inch LED Ceiling Wrap; Dual GFCI; 27K/30K/35K/40K/50K CCT Selectable; White Finish



#### GENERAL

|                           |                                                                                                                                                                                                                                                                                      |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Company                   | NUVO                                                                                                                                                                                                                                                                                 |
| EA Height                 | 4.65                                                                                                                                                                                                                                                                                 |
| EA Width                  | 2.76                                                                                                                                                                                                                                                                                 |
| EA Length                 | 18.31                                                                                                                                                                                                                                                                                |
| Bulb Included             | Integrated                                                                                                                                                                                                                                                                           |
| Extends (in)              | 2.51                                                                                                                                                                                                                                                                                 |
| Material                  | Steel                                                                                                                                                                                                                                                                                |
| Fixture Type              | Ceiling Wrap                                                                                                                                                                                                                                                                         |
| Status                    | Active                                                                                                                                                                                                                                                                               |
| Surge Protection          | Built-in surge protection - 2KV                                                                                                                                                                                                                                                      |
| Total Harmonic Distortion | <30%                                                                                                                                                                                                                                                                                 |
| CCT Selectable            | Yes                                                                                                                                                                                                                                                                                  |
| Wattage Selectable        | No                                                                                                                                                                                                                                                                                   |
| Finish Family             | White                                                                                                                                                                                                                                                                                |
| Additional Info           | Tamper Resistant Dual GFCI Outlet with 15 amp circuit with 14 gauge wire; 0.025 second GFCI Trip Time; The outlet is front facing, It has an easy to read diagnostic indicator; Built in protection against shock; Most used application for this product would be a bathroom vanity |
| Amps                      | 0.117A                                                                                                                                                                                                                                                                               |
| Has Camera                | No                                                                                                                                                                                                                                                                                   |
| Integrated Features       | Integratd Dual GFCI's                                                                                                                                                                                                                                                                |
| IOT Enabled               | No                                                                                                                                                                                                                                                                                   |
| Lens Finish               | White                                                                                                                                                                                                                                                                                |
| Lens Material             | Polycarbonate (PC)                                                                                                                                                                                                                                                                   |
| Lensed                    | Yes                                                                                                                                                                                                                                                                                  |
| Power Factor              | 0.9                                                                                                                                                                                                                                                                                  |
| SDS Class                 | LED_Fixture                                                                                                                                                                                                                                                                          |
| Indoor Outdoor            | Indoor                                                                                                                                                                                                                                                                               |
| Product Technology        | LED                                                                                                                                                                                                                                                                                  |
| Serviceable Battery       | No                                                                                                                                                                                                                                                                                   |
| Battery Indicator         | No                                                                                                                                                                                                                                                                                   |
| Digital Display           | No                                                                                                                                                                                                                                                                                   |

#### ELECTRICAL

|                     |                               |
|---------------------|-------------------------------|
| CCT (Kelvin Temp)   | 2700K/3000K/3500K/4000K/5000K |
| Dimmable            | Non-Dimmable                  |
| Hours Rated         | 50000                         |
| Beam Angle (degree) | 110                           |
| Color Temp          | Warm White to Natural Light   |
| CRI                 | 90+                           |
| Operating Frequency | 60Hz                          |
| Operating Temp      | -4F to +104F (-20C to +40C)   |
| Lumens              | 1298L-1391L                   |
| Volts               | 120v                          |
| Watts               | 14W                           |
| Max Lumens          | 1391L                         |

#### PHYSICAL

|                    |                |
|--------------------|----------------|
| Lamp Base          | Integrated     |
| Finish             | WHITE          |
| ANSI Base          | Integrated     |
| Lamp Type          | Integrated LED |
| Mounting Procedure | Ceiling/Wall   |

#### ADDITIONAL INFO

|                    |                                          |
|--------------------|------------------------------------------|
| Warranty           | 5-Years                                  |
| Installation Notes | Standard 3-inch and 4-inch Keyhole Slots |

#### PACKAGING

|               |                |
|---------------|----------------|
| UPC           | 045923624506   |
| Case Cube     | 0.9729         |
| Case Height   | 10.04          |
| Case Length   | 18.9           |
| Case Quantity | 6              |
| Case UPC      | 10045923624503 |
| Case Weight   | 15.23          |
| Case Width    | 8.86           |
| EA Cube       | 0.136          |
| EA Height     | 4.65           |
| EA Length     | 18.31          |
| EA Quantity   | 1              |
| EA Weight     | 2.54           |
| EA Width      | 2.76           |
| Pack Type     | Box            |
| Web Length    | 18.0           |
| Web Width     | 4.4            |

#### COMPLIANCE

|                   |                 |
|-------------------|-----------------|
| ADA Compliant     | Yes             |
| CA Prop 65        | Lead            |
| FCC Compliant     | Yes             |
| Location Rating   | Damp            |
| RoHS Compliant    | Yes             |
| Safety Listing    | cETLus          |
| California Ban    | Lawful for sale |
| Title 20          | Exempt          |
| T24/JA8 Compliant | No              |